

23-2**AUTOMATIC TRANSMISSION – Service Specifications/Lubricants/Special Tools****SERVICE SPECIFICATIONS**

Item		Standard value
A/T fluid temperature sensor resistance k Ω	At 0°C	16.7 – 20.5
	At 20°C	7.3 – 8.9
	At 40°C	3.4 – 4.2
	At 60°C	1.9 – 2.2
	At 80°C	1.0 – 1.2
	At 100°C	0.57 – 0.69
Damper clutch control (DCC) solenoid valve coil resistance (at 20°C) Ω		2.7 – 3.4
Low & reverse (LR) solenoid valve coil resistance (at 20°C) Ω		2.7 – 3.4
Second (2ND) solenoid valve coil resistance (at 20°C) Ω		2.7 – 3.4
Underdrive solenoid valve (UD solenoid valve) coil resistance (at 20°C) Ω		2.7 – 3.4
Overdrive solenoid valve (OD solenoid valve) coil resistance (at 20°C) Ω		2.7 – 3.4
Resistance of reduction (RED) solenoid valve coil at (20°C) Ω		2.7 – 3.4
Stall speed r/min	6G7	2,200 – 2,700
	4M4	2,400 – 2,900
Line pressure adjustment value kPa		1,010 – 1,050

LUBRICANTS

Item	Brand	Quantity L
Transmission fluid	DIA QUEEN ATF SP II M, ATF SP III or equivalent	9.3
Transfer oil	Hypoid gear oil SAE 75W-90 or 75W-85W conforming to API GL-4	2.8